

'Ram' Power Snare Setting Instructions

- ⇒ Read all instructions before proceeding.
- ⇒ Use every precaution when setting or unsetting the Ram Power Snare.
- ⇒ It is highly recommended to use the safety tools shown below.

To Unset the Spring



1.

Important - Maintain tension on the arms until the spring is completely open.




2.

- Remove snare cable before unsetting
- Maintain pressure on spring while unsetting.
- Firmly grasp eye ends of spring - one in each hand.
- Disengage safety catch while maintaining a firm grip and slowly release spring tension.



3.



Ram Foot


Stabilizes the spring and holds your safety catch upright.

1. Place spring eye in notch (a) as illustrated.
2. Bring safety catch up and place between steel pegs (b) as illustrated.
3. Bring the other arm down and engage the safety catch.


Setting the Spring



1. Place the arm with the safety clip on the ground. Using the Ram Foot will increase safety.



2. Make sure the safety catch is free. If using the Ram Foot, place the safety catch between the two steel pegs.



3. Place your foot on the bottom arm.

4. With your foot on the bottom arm force the other arm down until the safety clip can be engaged.



5. Pass the snare eye through the trigger eye of the power snare.

6. Hook it onto the lap link.

7. Rotate the lap link.

8. Place the cable in the trigger slot with the metal stop on the outside of the trigger.

9. Place the Ram Lok Plus as shown in illustration at top of page.


10. Adjust your snare loop size and height.

11. Carefully remove the safety clip.

12. Remove the Ram Lok Plus and your Ram Power Snare is set and ready.

RAM LOK PLUS Safety Tool

Illustration at right shows proper method for using the Ram Lok



Proper position for anchor

Ram Spring Support



When using the Ram in open areas, simply drive the support pin into the ground, then push the Ram coil spring on. This is a support only, you still have to anchor the Ram. (shown at top of page)

Ram Spring Treatment: Use Andy Stoe's Speed Dip or any good steel paint such as Tremclad. Allow 1 week drying time.

Snare Cable Treatment: To get a dull finish on your snares, coil snares in a pan, cover with water and add 2 tablespoons of baking soda. Simmer for 20 minutes, turn heat off and leave snares in water overnight. Rinse snares and hang to dry.

Ram Snaring Video

Full snaring course on video. Shows the set being made and the catch. Includes beaver snaring footage. Also available in French \$ 35.95

bert
RAM TRAP LTD.
RAM POWER SNARE SYSTEMS
BOX 172
BIRTLE, MANITOBA, CANADA R0M 0C0

Phone (204) 842-5189 Fax (204) 842-3287